


















FICHA TÉCNICA PRODUCTO- WALL TILE- POROSA BIII

MODELO	DAKOTA
COLOR	All color
ACABADO	Matt
FORMATO	310x980x11,4

	Test Standard UNE-EN ISO 10545	Product Standard ISO 13006-EN1441	DURSTONE VALUES
Características dimensionales <i>Dimensional and Surface Appearance</i>			
 Espesor <i>Thickness</i>	ISO 10545-2	± 10%	Cumple/Achieved
 Longitud y anchura <i>Length and width</i>	ISO 10545-2	± 0,30%	Cumple/Achieved
 Ortogonalidad <i>Squareness</i>	ISO 10545-2	± 0,50%	Cumple/Achieved
 Planaridad <i>Surface Flatness</i>	ISO 10545-3	± 0,50%	Cumple/Achieved
Propiedades físicas <i>Physical properties</i>			
 Absorción de agua <i>Water absorption</i>	ISO 10545-3	>10%	12,00%
 Resistencia a flexión N/mm² <i>Modulus of rupture</i>	ISO 10545-4	≥12 N/mm ²	15-20
 Carga de ruptura N <i>Breaking strength</i>	ISO 10545-4	≥600 N	≥600
 Resistencia a la abrasión superficial (PEI) <i>Resistance to surface abrasion (PEI)</i>	ISO 10545-7	-	NOT APPLY
 Resistencia al choque térmico <i>Resistance to thermal shock</i>	ISO 10545-9	Exigida/Required	Cumple/Achieved
 Resistencia al cuarteo <i>Crazing resistance</i>	ISO 10545-10	Exigida/Required	Cumple/Achieved
 Resistencia a la helada <i>Frost resistance</i>	ISO 10545-12	Exigida/Required	NOT APPLY
 Resistencia al rayado (MOHS) <i>Scratch resistance (MOHS)</i>	UNE EN-101	-	NOT APPLY
 Deslizamineto <i>Antislip</i>	ENV 12633	-	CLASE No aplica/Not Apply R
	DIN 51130	-	No aplica/Not Apply
	ANSI A 137.1	WET >42	DCOF No aplica/Not Apply PTV
	BS7976	-	No aplica/Not Apply
Propiedades químicas <i>Chemical properties</i>			
 Resistencia a productos de limpieza y aditivos <i>Resistance to household chemical ans swimming pool</i>	ISO 10545-13	Min. GB/UB	GA
 Resistencia a ácidos y bases <i>Resistance to acids and alkalis (low concentration)</i>	ISO 10545-13	GLB/ULB	GLA
 Resistencia a ácidos y bases <i>Resistance to acids and alkalis (high concentration)</i>	ISO 10545-13	GHB/UHB	GHA
 Resistencia a las manchas <i>Resistance to staining</i>	ISO 10545-13	Min. 3	5

CALIDAD Y PRODUCTO
CASA DEPOT, S.L.
DURSTONE CADE, S.L.