



VINTAGE COLLECTION
PRODUCT SPECIFICATIONS-TS EN 13329



Surface Stain Resistance	5 , (Group 1-2)	TS EN 438-2
	4 . (Group 3)	
Light Fastness	≤ 4 (Grey Scale)	TS 423-2 EN 20105-A02
Fire Resistance	E Class	TS EN 13329
Hight Difference Between Elements	Average ≤ 0,10 MAX. ≤ 0,15	TS EN 13329
Openings Between Elements	Averege ≤ 0,15 Max. ≤ 0,20	TS EN 13329
Mitter Deviation	≤ 0,20 mm	TS EN 13329
Surface Layer Straightness	≤ 0,30	TS EN 13329
Static Cavitation	≤ 0,05 (Permanent Crush)	EN ISO 24343-1
Wear Resistance/Class	AC5 / Class 33 ≥ 6000	TS EN 13329
Impact Resistance	≥ 15 N if ≥ 1000 mm	TS EN 13329
Moisture Content At The Time Of Dispatch From The Factory	% 4-10	TS EN 322
Thickness Swelling	≤ 15,0 %	TS EN 13329
Formaldehyde Emission	≤ 8 E1	TS EN 717-1
Thickness	8 ± 0,50 MM	TS EN 13329
Length	1290 MM ± 0,50 MM	TS EN 13329
Width	190 ± 0,10 MM	TS EN 13329
Density	≥890kg / m3	TS 64 EN 323
Tensile Resistance	≥ 1,50 N / mm2	TS EN 319
Bend Resistance	≥ 40 N/mm2	TS EN 310
Elasticity Module	≥ 3500 N/mm2	TS EN 310
Surface Soundness	≥ 1,25 N / mm2	TS EN 311

KKL.SPK.17
04.09.2018/00