

Certificado B.G.E.

Att.: Maderas del Alto Urgel SA
Tirso de Molina, 2
08940 Cornellà de Llobregat

04 de Agosto de 2020

Xavier Benguerel Pallarès, como representante legal de la empresa Bemon Grupo Empresarial S.L.
con NIF B63942619,

CERTIFICO:

Que nuestra empresa suministra anclajes para tarima tecnológica modelo 024
con tratamiento para la protección salina.

Este modelo de grapa consta de una base de hierro galvanizado al que se le aplica un tratamiento
de protección salina.

A continuación les enviamos, por una parte, el certificado de composición del hierro galvanizado
y, de forma anexa, el certificado de las características técnicas del tratamiento efectuado para
la protección salina.

COMPOSICIÓN Hierro Galvanizado

Carbono	C	0.012%
Manganeso	Mn	0.600%
Silicio	Si	
Fósforo	P	0.100%
Azufre	Si	0.045 %

CARACTERÍSTICAS MECÁNICAS

Alargamiento Lo=60	22%
Resistencia T Rm	270.50 N/mm2

Atentamente,

Xavier Benguerel
Administrador
Bemon Grupo Empresarial S.L.


QUALITY CERTIFICATE



Sistema de
Gestión
ISO 9001:2008
ISO 14001:2004
www.tuv.com
ID 9105019345



CERTIFICATE Nº. 30443



GRAPAS B.G.E.
C/JUAN CARANDELL Nº 1
08810 SANT PERE DE RIBES
BARCELONA

According to standard EN 10204-3,1/VW 91101

REFERENCE: BEMON PI	RULES: Standard
DELIVERY NOT 2679	DATE: 09/01/2017
SERIAL/LOT: S/L	PACKAGES: 6
ARTICLE: STAPLE	PARTS: 61000 KG: 1159
PROCESS: SHOT PENNING + DELTA PROTEKT KL-120+ DELTA SEAL GZ BLACK (PTFE)	

ORDER	FEATURES	REQUIRED	OBTAINED	PROCESS CONTROL
461,960,601	FREE CR.VI	OK	OK	SPECIFICATION SUPPLIER
461,960,601	ASPECT CORRECT	OK	OK	VISUAL
461,960,601	GRIP	OK	OK	GT0-GT01
461,960,601	COLOR	BLACK	BLACK	VISUAL
461,960,601	RED CORROSION RESISTANCE	1500h.	1500h.	SALINE FOG CAMERA
461,960,601	COATING THICKNESS	>12 microns	19,75 microns	METALLOGRAPHIC COURT
461,960,602	FREE CR.VI	OK	OK	SPECIFICATION SUPPLIER
461,960,602	ASPECT CORRECT	OK	OK	VISUAL
461,960,602	GRIP	OK	OK	GT0-GT01
461,960,602	COLOR	BLACK	BLACK	VISUAL
461,960,602	RED CORROSION RESISTANCE	1500h.	1500h.	SALINE FOG CAMERA
461,960,602	COATING THICKNESS	>12 microns	19,75 microns	METALLOGRAPHIC COURT
461,960,603	FREE CR.VI	OK	OK	SPECIFICATION SUPPLIER
461,960,603	ASPECT CORRECT	OK	OK	VISUAL
461,960,603	GRIP	OK	OK	GT0-GT01
461,960,603	COLOR	BLACK	BLACK	VISUAL
461,960,603	RED CORROSION RESISTANCE	1500h.	1500h.	SALINE FOG CAMERA
461,960,603	COATING THICKNESS	>12 microns	19,75 microns	METALLOGRAPHIC COURT

REMARKS:

[Handwritten signature]